

## Technical Data Sheet

### 3M™ Goggle Gear 500 Series Goggle

Products include: GG501SGAF - EU | GG500PI - EU

#### Product Description:

The 3M Goggle Gear 501 has a low profile design, an adjustable headband and optional prescription insert. The goggle features 3M™ Scotchgard™ Anti-Fog Coating which resists fogging for longer than traditional anti-fog coatings.

#### Intended Use:

These products are intended for protection against a variety of hazards including liquid droplets (3), large dust particles (4) and high speed particles at medium energy (B) at extremes of temperature -5°C and +55°C (T) in accordance with EN166:2001. In addition, this product also protect against UV radiation in accordance with EN170:2002.

#### Key Features:

- Optical class 1 lens suitable for prolonged use
- 3M Scotchgard anti-fog coating provides superior anti-fog properties, outperforming the N marking requirements of EN166.
- 3M Scotchgard anti-fog coating provides scratch resistance and durability, complying with the K marking requirements of EN166.
- Coating retains its effectiveness for at least 25 washes. Can be disinfected with diluted bleach soaking or alcohol wipes without losing its anti-fog performance.
- Offers excellent protection against UV radiation.
- Designed to be worn with Goggle Gear prescription inserts.

#### Applications:

These products can be used in a wide range of applications including:

- Manufacturing
- Metal working
- Mining/Oil & Gas
- Construction/outdoors
- Food industry

#### Standards and Approval:

The 3M™ Goggle Gear 501 goggle has been shown to meet the basic safety requirements under Article 10 of the European Community Directive 89/686/EEC and is thus CE marked.

These products have been examined at the design stage by ECS GmbH - European Certification Service, Huettfeldstrasse 50, 73430 Aalen Germany (Notified body number 1883).

These products are tested and CE approved against EN166:2001.



## Marking:

The 3M™ Goggle Gear 501 complies with the requirements of EN 166:2001 and associated standards and bear the following marks:

### Lens marking

Clear Polycarbonate 2C-1.2 3M 1 BT K N CE

### Frame marking

3M EN166 3 4 BT CE (without insert attached)  
3M EN166 3 4 FT CE (with Insert attached)

## Explanation of Marking

Marking	Description
2C-1.2 (EN 170:2002)	UV protection with good colour recognition. This product conforms to the requirements of the standard, providing UV protection for the complete specified range (210nm – 365nm).
1	Optical class
B	Impact protection against high speed particle at medium energy (120m/s)
F	Impact protection against high speed particles at low energy (45m/s)
T	Tested for impact protection at extreme temperature conditions -5°C and +55°C
3	Field of use: Liquid Product protects against liquid droplets or splashes
4	Field of use: Large dust particles Product protects against large dust particles (>5µm)
K	Resistance to surface damage by fine particles
N	Resistance to fogging

## Materials listing:

Component	Material
Lens	Polycarbonate
Frame (rigid)	Polypropylene
Frame (soft)	TPE
Headband	Nylon
Headband connector	Nylon
Goggle weight	50g
Prescription Insert	Polycarbonate

## Use limitation

- Never modify or alter this product.
- Do not use this product against hazards other than those specified in this document.
- These products are not suitable for welding.
- This product is NOT designed to be worn over prescription spectacles.



3М Украина  
03680, Киев, Украина  
ул. Н. Амосова, 12  
Бизнес центр «Горизонт Парк»  
Телефон: + 38 490 57 77  
Факс: +38 490 57 75  
Web-сайт: [www.3m.com/ua/siz](http://www.3m.com/ua/siz)  
После использования утилизировать.  
© 3M 2007. Все права защищены.



ООО «ИНТА» официальный дистрибьютор 3М в Украине  
03035 г. Киев, ул. Василия Липковского 1 Телефон: +38  
050 394 64 40, +38 044 337 84 17  
<https://inta.pro/ru/zacshita-organov-zreniya>